

COPY



1/4





FIG. 1



3/4




FIG. 3

4/4

$p = \text{BCP}(b, w, \alpha)$ *Bookmark-Coloring Process*
 Input: A bookmark b , a promotional amount w , a retention coefficient α .
 Output: BCV p .
 $p = 0$
 $p_b += \alpha \cdot w$
 if (stopping criterion is met) stop
 for all links $b \rightarrow j$ in L
 $p = p + \text{BCP}(j, (1 - \alpha) \cdot w / \deg(b), \alpha)$
 end for

FIG. 4

$p = \text{BCP}(b, \alpha, e)$ *Bookmark-Coloring Process*
 Input: A bookmark b , a retention coefficient α , and a tolerance threshold e .
 Output: BCV p .
 Initialize Q as a single pair queue $\{(b, 1)\}$
 $p = 0$
 while (Q is not empty)
 pop a queue Q element (i, w)
 $p_i += \alpha \cdot w$ // retained portion
 if ($w < e$) // stopping criterion
 continue // to beginning of while-loop
 $z = (1 - \alpha) \cdot w / \deg(i)$ // distributed amount
 for all links $i \rightarrow j$ in L // i is fixed: direct link access
 if (pair (j, s) is present in Q) // direct Q access
 $s += z$ // existent element update
 else // no j element in the queue
 add a new pair (j, z) to Q // new queue element
 end for
 end while

FIG. 5

$[v, s] = \text{BC}(b, w, \alpha | H)$ *H-Relative Conceptual Bookmark-Coloring Process*
 Input: A bookmark $b \notin H$, an amount w , a coefficient α , and a hub H .
 Output: H -relative BCV v and blocked s .
 $v = 0, s = 0$
 if ($b \in H$)
 $s_b += w$
 else
 $p_b += \alpha \cdot w$
 if (stopping criterion is met) stop
 for all links $b \rightarrow j$ in L
 $[v, s] = [v, s] + \text{BCP}(j, (1 - \alpha) \cdot w / \deg(b), \alpha | H)$
 end for
 end else

FIG. 6



4/4

$p = \text{BCP}(b, w, \alpha)$ Bookmark-Coloring Process
 Input: A bookmark b , a promotional amount w , a retention coefficient α .
 Output: BCV p .
 $p = 0$
 $p_b += \alpha \cdot w$
 if (*stopping criterion is met*) stop
 for all links $b \rightarrow j$ in E
 $p = p + \text{BCP}(j, (1 - \alpha) \cdot w / \text{deg}(b), \alpha)$
 end for

FIG. 4

$p = \text{BCP}(b, \alpha, e)$ Bookmark-Coloring Process
 Input: A bookmark b , a retention coefficient α , and a tolerance threshold e .
 Output: BCV p .
 Initialize Q as a single pair queue $\{(b, 1)\}$
 $p = 0$
 while (Q is not empty)
 pop a queue Q element (i, w)
 $p_i += \alpha \cdot w$ // retained portion
 if ($w < e$) // stopping criterion
 continue // to beginning of while-loop
 $z = (1 - \alpha) \cdot w / \text{deg}(i)$ // distributed amount
 for all links $i \rightarrow j$ in E // i is fixed: direct link access
 if (pair (j, s) is present in Q) // direct Q access
 $s += z$ // existent element update
 else // no j element in the queue
 add a new pair (j, z) to Q // new queue element
 end for
 end while

FIG. 5

$[v, s] = \text{BC}(b, w, \alpha | H)$ H-Relative Conceptual Bookmark-Coloring Process
 Input: A bookmark $b \notin H$, an amount w , a coefficient α , and a hub H .
 Output: H -relative BCV v and blocked s .
 $v = 0, s = 0$
 if ($b \in H$)
 $s_b += w$
 else
 $p_b += \alpha \cdot w$
 if (*stopping criterion is met*) stop
 for all links $b \rightarrow j$ in E
 $[v, s] = [v, s] + \text{BCP}(j, (1 - \alpha) \cdot w / \text{deg}(b), \alpha | H)$
 end for
 end else

FIG. 6